

# POS 360 Series

The POS 360 series is an innovative "Fanless" design that operates at low noise, low power consumption and minimal maintenance. Tool-less modular construction is easy to maintain and service, and therefore significantly reduces total cost of ownership. Its small footprint and VESA wall-mountable features are ideal for applications where space is at a premium.

- Low power consumption and fanless for quiet operation
- Easy access mechanical design for HDD and Compact Flash maintenance and upgrades
- Integrated wall-mount VESA design for wall mount applications
- Optional peripherals such as MSR, Programmable Keypad, Customer Display and 2nd Display are available for challenging operating environments
- All-in-one MB design for I/O card and cable material cost reductions



## Features



1. Small footprint 280 (W) x 250 (D)



2. Easy HDD & Motherboard access



3. VESA wall - mountable



4. Magnetic Strip Card Reader



5. Programmable Keypad (32 keys) / Magnetic Strip Card Reader / Smart IC Card Reader



6. Second Display (7", 8.4", 10", 12.1" TFT LCD) or Customer Display (VFD or LCD)

## POS 360 Series



### Specification

Model Name	POS 362	POS 365
Motherboard	B78	
CPU	Celeron M ULV 1GHz	
Chipset	Intel 852GM FSB 400MHz / ICH4	
System Memory	1 x DDR SO-DIMM Slot Up to 1GB	
Graphic Memory	System Memory Shared Up to 64MB	
LCD Panel		
LCD Size	12.1" TFT	15" TFT
Brightness	150 - 400 cd / m <sup>2</sup>	250 cd / m <sup>2</sup>
Maximal Resolution	800 x 600 / 1024 x 768	1024 x 768
Touch Screen Type	Resistive	
Tilt Angle	-25° ~ 65°	
Storage		
HDD	1 x 2.5" slim HDD bay or 3.5" HDD bay	
Flash Memory	Compact Flash Memory Option (Type I & II)	
Expansion	1 x mini-PCI	
External I/O		
USB 2.0	4 x USB Type A	
Serial / COM	4 x COM ports RJ-45 connectors (COM 1 & COM 2 standard RS-232; COM3 & COM4 pin 9 with 5V or 12V power by jumper)	
Parallel	1 x DB 25F	
LAN (10 / 100)	1 x RJ45	
2" VGA	1 x DB 15F	
Cash Drawer	1 x RJ11 (12V / 19V)	
Audio	1 x Line-in / 1 x Line-out	
Control / Indicator		
Power Button	1	
LED Indicator	1	
Power		
Power Adapter	External 90W AC	
Peripheral		
Customer Display	VFD / LCD Pole Display	
Second Display	7" / 8.4" / 10" / 12.1" TFT LCD	
Magnetic Card Reader	3 Tracks (RS-232 / PS2 interface)	
Programmable Keypad / Card Reader	32 keys with key lock / Magnetic Card Reader (PS2 Interface) / Smart IC Card Reader (USB Interface)	
Environment		
EMC & Safety	FCC Class A / CE Marking / LVD	
Operating Temperature	5°C ~ 35°C ( 41°F ~ 95°F )	
Storage Temperature	-20°C ~ 55°C (-4°F ~ 131°F)	
Operating Humidity	20% - 80% RH non-condensing	
Storage Humidity	20% - 85% RH non-condensing	
Dimension (W x D x H)	POS362: 308 x 265 x 325 mm (12.1" x 10.4" x 12.8")	POS365: 385 x 265 x 384 mm (15.2" x 10.4" x 15.1")
OS Support	Windows XP, WEPOS, XP Embedded, XP Professional for Embedded, Windows 2000 Professional Embedded, WIN NT 4.0, Linux, Redhat 7.2	

Product specifications subject to change without prior notice.

©2008 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.



**PRO-AN**  
保雅電腦

香港新界火炭坳背灣街38-40號華衛工貿中心7樓10-12室  
Room 10 - 12, 7/F., Wah Wai Centre, 38 - 40 Au Pui Wan Street, Fo Tan, N.T., Hong Kong.  
Tel : (852) 2609-2666 Fax : (852) 3747-4759 <http://www.posHK.com>